

FLATBED LASER MFC-9180

Plain Paper Fax Features

- **8MB Memory** stores up to 500 pages* for out-of-paper reception
- **Memory Security** helps to prevent unauthorized access to the fax machine by activating a 4-digit password
- **14.4k bps High Speed Fax Modem**
- **Dual Access** lets you scan a fax into memory while another is being sent or received
- **Broadcasting up to 150 locations**
- **Up to 30 Sheets Automatic Document Feeder**
- **Up to 200 Sheets Plain Paper Cassette Tray**
- **100 Stations Automatic Memory Dialling**
- **Electronic Cover Page**
- **"Smoothing" Enhanced Image Resolution**
- **Delayed Transmission up to 50 timers**
- **64 Shade Grey Scale** for Photography Transmission
- **Error Correction Mode**
- **Remote Fax Retrieval and Fax Forwarding**
- **Polling**

Digital Copier Features

- Up to 10 copies per minute copy speed
- 600 dpi class copy quality output (interpolated resolution)
- Multi-copying up to 99 copies
- Copy reduction or enlargement from 25% to 400% in one percent increment
- Stack or Sort Functions
- 2-in-1, 4-in-1 Reduction or Poster Enlargement

* Using Brother #1 Chart with MMR Coding and Standard Resolution

** For Windows® only

PC Fax Receiving Feature is not available

▲ Due to the restrictions of OS or applications, scanning at or above 2400 x 2400 dpi may not support all sizes of documents or images.

Laser Printer Features

- True 600 x 600 dpi laser output
- Up to 10 page per minute print speed
- Prints A4, letter, legal, B5, A5, Executive, OHP and Envelopes
- Parallel and USB Interface standard
- Bonus Parallel Cable included

Colour Scanner Features

- Up to 9600 x 9600 dpi[▲] scanning (interpolated resolution)
- 600 x 2400 dpi scanning (optical resolution)
- Includes ScanSoft™ Paperport® and Textbridge® OCR Software
- Scan to E-mail** / OCR** / Image **

PC Fax Features

- Brother PC Fax Driver for sending faxes via your PC
- Broadcasting from your PC

Optional Accessories

- DR - 8000 : Drum Unit
- TN - 8000 : Toner Cartridge

COMPUTER REQUIREMENT

For Windows®				
Operating System	CPU	Minimum RAM	Recommended RAM	Hard Disk Space
95, 98, 98SE	75 MHz	24MB	32MB	50MB
NT® Workstation 4.0	75 MHz	32MB	64MB	50MB
2000 Professional	133 MHz	64MB	128MB	50MB
Me	150 MHz	32MB	64MB	50MB
For Macintosh®				
Operating System	CPU	Minimum RAM	Recommended RAM	Hard Disk Space
Apple® Macintosh® QuickDraw®				
G3, G4, iMac or iBook with OS 8.5, 8.5.1 (Only Printer)		All base models meet minimum requirement		50MB
OS 8.6/9.0/9.0.4/9.1 (Printer & Scanner)				

Specifications

Type	: Desktop Facsimile Transceiver
Compatibility	: ITU-T Group 3
Coding system	: MH/MR/MMR
Modem speed	: 14400 - 2400bps; Automatic Fallback
Transmission Speed	: 6 seconds *
Document Input Width	: 148mm to 216mm(ADF) Max 216(Scanner)
Document Input Length	: 148mm to 356mm(ADF) Max. 297(Scanner)
Scanning/Printing Width	: 208mm
Automatic Document Feeder (ADF)	: Up to 30 sheets
Multi-Purpose Sheet Feeder	: Up to 200 sheets
Grey Scale	: 64 levels (Error Diffusion)
Display	: LCD, 16 characters x 2, Backlit
Polling Types	: Standard, Secure, Delayed, Sequential
Contrast Control	: Automatic / Light / Dark (manual setting)
Resolution	: • Horizontal 8 dots/mm • Vertical Standard - 3.85 lines/mm • Fine, Photo -7.7 lines/mm 15.4 lines/mm
Speed Dial	: 100 stations
Automatic Redial	: 10 times at 3 minute Intervals
Speaker Type	: Monitor
Automatic Answer	: 0 -10 rings
Communication Source	: Public Switched Telephone Network (PSTN)

Printer Specifications

Emulation	: Brother Printing System for Windows®, emulation mode of HP LaserJet 5P (PCL level 5e)
Printer Driver	: Windows® 95, 98, 98SE, Me, 2000 professional and Windows NT® Workstation Version 4.0 driver supporting Brother Native Compression mode and bi-directional capability. Apple® Macintosh® QuickDraw® Driver for OS™ 8.5 / 8.5.1 / 8.6 / 9.0 / 9.0.4 / 9.1
Interface	: Bi-directional parallel cable (IEEE-1284) USB (Universal Serial Bus) Interface
Printer Method	: Electrophotography by semiconductor laser beam scanning
Resolution	: 600 dots/inch
Print Speed	: Up to 10 pages/minute (when loading A4 paper from the multi-purpose sheet feeder)

Electrical and Environment

Temperature	: (Allowable) 10 - 32.5°C (Storage) 0 - 40°C
Power Source	: 220 - 240V AC 50/60Hz
Power Consumption	: Operating (Copying); 260W or less (25°C) Peak : 940W Sleep Mode : 15W or less Stand by : 75W or less (25°C)
Noise	: Operating : 52 dB A or less Stand by : 39 dB A or less
Humidity	: Operating : 35 to 80% (without condensation) Storage : 20 to 80% (without condensation)
Dimensions	: 459 x 458 x 354 mm
Weight	: 11 kg