


FLATBED LASER MFC-9160



FEATURES

SPECIFICATIONS

Digital Copier Features

- Up to 10 copies per minute copy speed
- 600 dpi class copy quality output (interpolated resolution)
- Up to 200 sheets paper cassette tray
- Up to 30 pages automatic document feeder
- Multi-copying up to 99 copies
- Copy reduction or enlargement from 25% to 400% in one percent increment
- Stack or Sort Functions
- 2-in-1, 4-in-1 Reduction or Poster Enlargement

Laser Printer Features

- True 600 x 600 dpi laser output
- Up to 10 pages per minute print speed
- Prints A4, letter, legal, B5, A5, Executive, OHP and Envelopes
- Parallel and USB Interface standard
- Bonus parallel cable included
- PLC5e® Emulation

Colour Scanner Features

- Up to 9600 x 9600 dpi** scanning (interpolated resolution)
- 600 x 2400 dpi scanning (optical resolution)
- Scan to E-mail* / OCR* / Image*
- Includes Scansoft™ PaperPort® and Textbridge® OCR Software

Optional Accessories

- DR - 8000 : Drum Unit
- TN - 8000 : Toner Cartridge

COMPUTER REQUIREMENT

For Windows®

Operating System	CPU	Minimum RAM	Recommended RAM	Hard Disk Space
95, 98, 98SE	75 MHz	24MB	32MB	50MB
NT® Workstation 4.0	75 MHz	32MB	64MB	50MB
2000 Professional	133 MHz	64MB	128MB	50MB
Me	150 MHz	32MB	64MB	50MB

For Macintosh®

Operating System	CPU	Minimum RAM	Recommended RAM	Hard Disk Space
Apple® Macintosh® QuickDraw® G3, G4, iMac or iBook with OS 8.5, 8.5.1 (Only Printer) OS 8.6/9.0/9.0.4/9.1 (Printer & Scanner)	All base models meet minimum requirement			50MB

General Specifications

Document Input Width	: 148mm to 216mm (ADF) Max. 216 (Scanner)
Document Input Length	: 148mm to 356mm (ADF) Max. 297 (Scanner)
Scanning/Printing Width	: 208mm
Automatic Document Feeder (ADF)	: Up to 30 sheets
Multi-Purpose Sheet Feeder	: Up to 200 sheets
Display	: LCD, 16 characters x 2, Backlit
Memory	: 8MB
Dimensions (WxDxH)	: 459 x 458 x 354mm
Weight	: 11 kg

Printer Specifications

Emulation	: Brother Printing System for Windows®, emulation mode of HP LaserJet 5P (PCL level 5e)
Printer Driver	: Windows® 95, 98, 98SE, Me, 2000 professional and Windows NT® Workstation Version 4.0 driver supporting Brother Native Compression mode and bi-directional capability. Apple® Macintosh® QuickDraw® Driver for OS™ 8.5 / 8.5.1 / 8.6 / 9.0 / 9.0.4 / 9.1
Interface	: Bi-directional parallel cable (IEEE-1284) USB (Universal Serial Bus) Interface
Printer Method	: Electrophotography by semiconductor laser beam scanning
Resolution	: 600 dots/inch
Print Speed	: Up to 10 pages/minute (when loading A4 paper from the multi-purpose sheet feeder)
Electrical and Environment	
Temperature	: (Allowable) 10 - 32.5°C (Storage) 0 - 40°C
Power Source	: 220 - 240V AC 50/60Hz
Power Consumption	: Operating (Copying); 260W or less (25°C) Peak : 940W Sleep Mode : 15W or less Stand by : 75W or less (25°C)
Noise	: Operating : 52 dB A or less Stand by : 39 dB A or less
Humidity	: Operating : 35 to 80% (without condensation) / Storage : 20 to 80% (without condensation)

* For Windows® only

** Due to the restrictions of OS or applications, scanning at or above 2400 x 2400 dpi may not support all sizes of documents or images .