





Plain Paper Fax + α

LASER FAX-2850






UNIQUE BROTHER FEATURES

- Memory Security**
 helps to prevent unauthorised access to the fax machine by activating a 4-digit password.
 


- 14.4k bps High Speed Fax Modem**

- Dual Access**
 allows you to scan up to 50 pages of document into memory while the fax machine is receiving or sending another fax (from memory).
 
- Remote Fax Retrieval**
- Fax Forwarding**
 to any other fax machine with the Group 3 facsimile.
- Electronic Cover Page**
 generates 4 pre-programmed and 2 programmable messages.
- Reports Key & Search Key**
- Enhanced Remote Activation**
 allows you to transfer a fax call from any single line phone extension in the house.
- "Smoothing" Enhanced Image Resolution**
 removes the rough edges from text and makes incoming documents easier to read.
- On Screen Programming**
- Caller ID Ready ***
- Distinctive Ring Detection***

STANDARD FEATURES

- 2MB Memory**
 stores up to 90 pages** for out-of-paper reception.
 
- Broadcasting**
 up to 158 locations.
 
- Error Correction Mode**
- Delayed Transmission up to 50 Timers**
- Up to 20 Page Automatic Document Feeder**
- Up to 200 Sheet Plain Paper Cassette Tray**
- FAX/TEL Auto Switching**
- Answering Machine Interface**
- Auto Reduction for Incoming Documents**
- 8 One-Touch /100 Speed-Dial Locations**
- 16 Digit LCD Display**
- Polling**
- 64 Shade Gray Scale for Photography Transmission**

- Activity Reports and Transmit Verification Reports**
- Page Header with Time / Date / Sender ID & Page Number**
- Built-in telephone Handset & On-Hook Dialing**
- Personal Copier Functions**
 - Multi-copying up to 99 copies
 - Enlargements up to 200% in 1% increments
 - Reductions down to 50% in 1% increments
 - 2 in 1 / 4 in 1 Special Copy

SPECIFICATIONS

Type:	Desktop Facsimile Transceiver
Compatibility :	ITU-T Group 3
Coding System :	MH/MR/MMR
Modem Speed :	14400/12000/9600/7200/4800/2400bps; Automatic Fallback
Transmission Time :	6 seconds**
Document Input Width :	148 mm to 216 mm
Document Input Length :	100 mm to 360 mm
Scanning/Printing Width :	208 mm
Paper Size :	Letter / Legal / A4
Multi-purpose Sheet Feeder :	Up to 200 sheets
Printer Type :	Laser Printer
Gray Scale :	64 levels
Polling Types :	Standard, Secure, Delayed, Sequential
Contrast Control :	Automatic / Light / Dark (manual setting)
Resolution :	<ul style="list-style-type: none"> Horizontal - 8 dots/mm Vertical Standard - 3.85 lines/mm Fine, Photo- 7.7 lines/mm Superfine, Photo (copy) - 15.4 lines/mm
One Touch Dial :	8 stations
Speed Dial :	100 stations
Automatic Redial :	10 times at 3 minute intervals
Speaker Type :	Monitor
Auto Answer :	0-10 rings
Communication Source :	Public switched telephone network (PSTN)
Print Method :	Electrophotography by semiconductor laser beam scanning
Electrical and Environment	
Temperature :	(Allowable) 10 - 32.5°C (50 - 90.5°F) (Storage) 0 - 40°C (32 - 104°F)
Power Source :	220 - 240V AC 50/60Hz
Power Consumption :	Operating (Copying): 260W or less (25°C) Peak : 940W Sleep Mode : 10W or less Standby : 70W or less (25°C)
Noise :	Operating : 50 dB A or less Standby : 39 dB A or less
Humidity :	Operating : 20 - 80% (without condensation) Storage : 10 - 90% (without condensation)
Dimensions :	395 x 359 x 243mm
Weight :	7.5 kg

OPTIONAL ACCESSORIES

- DR - 8000 : Drum Unit
- TN - 8000 : Toner Cartridge

* These features are not available in some countries

** Using Brother #1 Chart, with MMR coding and Standard Resolution