

FAX-335MC



Features

MESSAGE CENTER FEATURES

Selection modes

Message Center mode allows you to store incoming fax and voice messages in a flexible memory. Message Center mode offers you six flexible memory settings, so that you can decide which kinds of messages you want to receive.



Answering Machine Features

- Built-in answering machine with up to 15 minutes of recording time.
- Remote access with ID code.
- Quick access (Play/Erase/Skip/Repeat).
- Toll saver.
- Voice alarm allows you to record a message on the fax machine and have it played back at a time you specify.


Fax Memory Features

- **512KB memory stores up to 20 pages# for Out-of-Paper Reception**
- Broadcasting up to 104 locations
- Quick-Scan
- Error Correction Mode
- Remote retrieval of stored fax messages from any other fax machine
- Fax forwarding to any other fax machine with the group 3 facsimile
- Paging function works with most national and regional pagers*




Unique Brother Features




- **Key Lock System** enables the machine to cease sending fax/making a phone call/copy when key-lock is activated, using 4 digit password. 
- **Multi Ringing Sound** Lets you select your music out of four choices for rings. 
- **Call Reservation** allows you to send a fax and then at the end of transmission, you can talk to the other party.
- **Call Back Message** allows you to send a fax and then leave a message for the party to call you back.
- **Anti-Junk Function*** enables you to prevent unwanted junk fax or call by storing the number in the station memory. This saves paper by not printing out unwanted junk faxes. 

- **Night Mode** receives incoming calls without ringing. 

* Using ITU-T Test Chart #1 with MH coding in ECM mode.
* Please check with local phone company for the availability of these services.

- **Anti-Curl System (ACS)** flattens paper and prevents annoying curling problems. 
- **Electronic CoverPage** generates 4 pre-programmed and 2 programmable messages.
- "Smoothing" Enhanced Image Resolution
- 14.4k bps High Speed Modem
- Auto CNG Tone Detection (Easy Receive)
- Full Duplex Digital Speaker Phone
- Multi Resolution Transmission
- Enhanced Remote Activation
- Next-Fax Reservation
- Help Key & Search Key
- Hold on Music
- Caller ID Ready* / Caller ID Log*
- Distinctive Ring Detection*

Standard Features

- Automatic paper cutter 
- FAX/TEL auto switching
- 104-station auto dialing
- 64 shade gray scale for photograph transmission
- 16 digit LCD display
- Polling
- 50m paper roll capacity 
- Multi-copying with sorting
- TAD Interface
- Automatic 10 pages document feeder 
- Transmission verification reports
- On-hook dialing
- Function as a fax, telephone and copier
- Journal reports
- Built-in telephone handset
- Page header with time/date/sender ID and page number

Option

- **Model CT-70 Catch Tray For Original Documents**
Easily attaches to the front of the fax machines and neatly stacks all original documents.

Specification

Type	: Desktop facsimile transceiver
Compatibility	: ITU-T Group 3
Coding System	: Modified Huffman (MH)
Modem Speed	: 14400/12000/9600/7200/4800/2400bps; Automatic Fallback
Transmission Time	: 9 secs (Brother proprietary mode)
Document Input Width	: 148mm to 216mm
Scanning/Printing Width	: 208mm
Paper Roll Size (width)	: 216mm
(length)	: 50m standard thermal paper roll capacity
Printer Type	: Line Thermal
Gray Scale	: 64 levels (Dithered)
Paper Cutter	: Automatic
Display	: LCD, 16 characters
Polling Types	: Standard, Delayed, Secure
Contrast Control	: Automatic/Super Light/Super Dark (manual setting)
Resolution	: Horizontal – 8 dot/mm (203 dot/inch) Vertical Standard – 3.85 line/mm (98 line/inch) Fine, Photo – 7.7 line/mm (196 line/inch) Superfine, Photo (copy) – 15.4 line/mm (392 line/inch)
One Touch Dial	: 4 stations
Speed Dial	: 100 stations
Automatic Redial	: 3 times at 5 minute intervals
Speaker Type	: Full Duplex, Digital
Auto Answer	: 0 ~10 rings (0-4 rings in some countries)
Communication Source	: Public switched telephone network
Operating Environment	: 5° - 35° C (41 - 95° F)
Power Source	: 220 ~ 240V AC 50/ 60Hz
Power Consumption	: Standby: under 3.5 watts Peak: under 110 watts
Dimensions	: 299(W) x 240(D) x 137(H)mm
Weight	: 2.9 kg