

Basic Specification

GP335 Main Unit

Type	Desktop
Printing system	Laser dry electrostatic transfer
Resolution	1200dpi equivalent x 600dpi
CPU	MIPS R5000 (NEC), 200 MHz
RAM	32 MB
Supported PDL	Postscript [®] 3, PCL5e
Internal fonts	136 types
Hard disk	2.5 inch IDE 2.1 GB
Operating System	Win 95, Win 98, Win NT 4.0 Mac OS 8.5 UNIX:Sun, Solaris (LPD)
Network Interfaces	100 BASE-T, 10 BASE-T AUI, Token Ring (optional)
Network Protocols	IPX / SPX, Apple Talk, TCP / IP, NetBIOS (over TCP / IP)
Print speed	33 pages per minute: A4 / B5 / A5R 20 pages per minute: A3
Warm up time	81 seconds or less (from power off at 20 deg C)
Fixing system	Heated Rollers
Power consumption	230V: 1.5 kW or less
Paper capacity	Standard: 50 sheets x 2, 50 sheets bypass Maximum: 500 sheets x 4, Side paper deck (3500 sheets), 50 sheets bypass
Scanning sizes	Original: up to A3
Scanning Zoom	25-800%
Photoconductor	OPC
Dimension (W x D x H)	1194 x 720 x 539 mm
Installation space	1194 x 720 mm
Weight	83.4 kg

Finisher-C1 (optional)

Paper size	A3, A4, A4R, A5, A5R, A6, B4, B5, B5R 11" x 17", LGL, LTR, LTRR, STMT, STMT(R)
Stacking capability	1500 sheets: A4, A5(R), B5, LTR, STMT(R) 750 sheets: A3, A4R, B4, B5R, 11" x 17", LGL, LTRR
Stapling capability	50 sheets: A4, B5, LTR 30 sheets: A3, A4, B4, B5, 11" x 17", LGL, LTR
Stapling size	Corner stapling: A3, A4(R), B4, B5, 11" x 17", LGL, LTR(R) Double stapling: A3, A4, B4, B5, 11" x 17", LGL, LTR
Power consumption	170W or less (powered from main unit)
Dimensions (W x D x H)	667mm x 582mm x 1047mm
Installation space (W x D)	162mm x 720mm
Weight	Approx. 32kg

*1 Combined total stacking capacity of Trays A, B, C.

Duplex Auto Document Feeder-A1

Acceptable paper size	A3 / 11" x 17" - B5(R) / STMT
Acceptable paper thickness	50g/m ² - 150g/m ²
Acceptable sheet quality	50 sheets: A4, A4R, B5, B5R, A5, LTR, LTRR, STMT 25 Sheets: A3, B4, 11" x 17", LGL
Feeding Speed *1	33 sheets per minute (A4 / LTR)
Power consumption	170W or less (powered from main unit)
Dimension (W x D x H)	645mm x 521mm x 150mm
Weight	Approx. 14.8kg

*1 Feeding speed is coordinated with the main unit's scanning speed.

Fax Board (optional)

Telephone line used	Public telephone network, facsimile communication network
Maximum original size	A3 / 11" x 17"
Sending sizes	A3, A4, A4R, A5, A5R, A6, B4, B5, B5R 11" x 17", LGL, LTR, LTRR, STMT, STMT(R) DADF: Two-sided originals possible
Maximum receiving size	A3 / 11" x 17"
Paper size	A3 / 11" x 17" - B5(R) / STMT(R)
Transmission speed	2.8 seconds at 33,600bps
Modem speed	FAX modem: 33600, 14400, 1200, 9600, 7200, 4800, 2400bps
Compatibility	G3
Memory capacity	32 MB (standard Canon chart: approx. 640 sheets) Optional memory: 32MB (total 64MB: approx. 1000 sheets) 64MB (total 96MB: approx. 1000 sheets)
Sequential broadcasting	Up to 216 destination (One-touch Speed Dialing: 60; Coded Speed Dialing with the Number Keys: 16)

*1 ECM-MMR/A4 size, using standard Canon originals.

Multi-Output Tray-D1 (optional)

Acceptable paper size	A3 / 11" x 17" - B5(R)/STMT
Paper capacity	300 sheets (100 sheets x 3 trays)
Power consumption	40W or less (powered from main unit)
Dimension (W x D x H)	476mm x 498mm x 264mm
Installation space (W x D)	1430mm x 720mm
Weight	Approx. 14.8kg

Other optional accessories


• Network Printer Board-K1 • SCSI Interface Board-D1 • DADF-B1 • Cassette Feeding Unit-S1 • Side Paper Deck-B1 • Finisher-E1 • Control Card V




Finisher-C1



Saddle Finisher-C2



Cassette Feeding Unit R1



Multi Output Tray D1