

Basic Specification

GP605 Main Unit

Type	Desktop
Printing system	Laser dry electrostatic transfer
Exposure system	Twin laser beam
Resolution	1200dpi equivalent x 600dpi
CPU	MIPS R5000 (NEC), 200 MHz
RAM	32 MB
Supported PDL	Postscript®3, PCL5e
Internal fonts	136 types
Hard disk	2.5 inch IDE 2.1 GB
Operating System	Win 95, Win 98, Win NT 4.0 Mac OS 8.5 UNIX:Sun, Solaris (LPD)
Network Interfaces	100 BASE-T, 10 BASE-T AUI, Token Ring (optional)
Network Protocols	IPX / SPX, Apple Talk, TCP / IP, NetBIOS (over TCP / IP)
Print speed	60 pages per minute: A4 / B5 / A5R 30 pages per minute: A3
Warm up time	5 minutes or less (from power off at 20 deg C)
Fixing system	Heated Rollers
Power consumption	230V: 1.5 kW or less
Paper capacity	Front paper drawers: 1500 sheets x 2 Paper cassettes: 550 sheets x 2 Stack bypass: 50 sheets
Paper thickness	60-200 gsm
Scanning sizes	Original: up to A3
Scanning Zoom	25-400%
Photoconductor	OPC
Dimension (W x D x H)	764 x 795 x 1137 mm
Installation space	1416 x 795 mm
Weight	251 kg

GP 605

Finisher-D1 (optional)

Paper weights	64g/m ² - 2 00g/m ²
Stacking capacity: Tray A	A3 / 11" X 17" - Postcard: 250 sheets
Stacking capacity: Tray B	A4, A5, A5R, LTR, STMTR: 2000 sheets A3, B4, 11" x 17" LGL: 1000 sheets
Stapling sizes	Single stapling (50 sheets): A3, A4, B4, B5, 11" x 17" LGL, LTR Double stapling (50 sheets): A3, A4, B4, B5, 11" x 17", LTR
Power consumption	250W (maximum)
Power supply	230V
Dimensions (W x D x H)	655mm x 708mm x 995mm
Installation space (W x D)	1738mm x 795mm (when attached to main unit)
Weight	Approx. 60kg

Side Paper Deck-C1 (optional)

Paper capability	3500 sheets (80g/m ²)
Dimensions (W x D x H)	323mm x 583mm x 519mm
Weight	Approx. 41kg
Acceptable paper sizes	A4 / B5 / LTR

Automatic Document Feeder (standard)

Acceptable paper size	Original tray: A3 / 11" x 17" - A5 / STMT (50g/m ² - 200g/m ²) SADF tray: A3 / 11" x 17" - A5 / STMT (38g/m ² - 200g/m ²)
Acceptable sheet quality	A3, B4, 11" x 17", LGL: 50 sheets (80g/m ²) A4, A4R, B5, B5R, A5, LTR, LTRR, STMT: 100 sheets (80g/m ²)
Feeding Speed	55 sheets per minute (A4 / LTR)
Power supply	DC24V (from main unit)
Dimension (W x D x H)	645mm x 569.5mm x 143mm
Weight	Approx. 21kg (not including output tray)

Other optional accessories

- Saddle Finisher-D2 • Cover Insertion Unit-A1 • Paper Folding Unit-B1
- Copy Tray Unit-D1 • Document Tray-D1 • ASSIST-II V II • Control Card-V